

G503504C2

DC Led Power Supply MINI-4-700mA 4W IP65

April 04th, 2025, 14:09



DESCRIPTION

IP65 Led power supply to incorporate with 700mA constant current output. Output voltage from 6 to 12Vdc. Power range from 2.1 to 4.2W. Primary and secondary wiring with 18cm of UL1015 22AWG cable. Class II. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure.

PRICE

Lot	P.V.P. excluding VAT
1	6,37€
5	5,27€
10	4,78€
50	4,54€

Continued on next page >>

G503504C2

DC Led Power Supply MINI-4-700mA 4W IP65

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CB



Weight: 45 Grams

Packging: Box 1 Unit

NOTES

ECO ERP Design. IP65. Constant current output 700mA

OTHER FEATURES

Length (mm): 48

High (mm): 21

Voltage In (Vac): 220~240

Intensidad Out (A): 0.7

Power (W): 2.1~4.2

Critical Temperature (°C): 85

Dimmable: NO

Width (mm): 27

Colour: White

Voltage Out (Vdc): 2.5~6

Frecuency (Hz): 50~60

Room Temperature (°C): -20~+60

Ingress Protection: IP65

Power factor: 0.60

DOCUMENTS

 [Data Sheet](#)

 [Report](#)

 [Report](#)

 [DC Led Power Supply MINI-4-700mA 4W IP65](#)

 [ROHS](#)

 [CB](#)

 [CE](#)

 [EMC TUV CERTIFIED](#)

 [Safety TUV CERTIFIED](#)