

G503506L

DC Led Power Supply MINI-6-250mA 6W

February 01st, 2025, 20:32



DESCRIPTION

IP65 LED power supply for incorporation with constant current output 250mA.6W Output voltage from 12 to 24Vdc. Primary wiring with 18cm of VDE 7726 0.5mm² cable and secondary wiring with 18cm of UL 1015 22AWG cable. Class II. Protection against open circuit, short circuit, overload and over temperature. Automatic reset in case of failure.

PRICE

	Lot	P.V.P. excluding VAT
	1	6,47€
	5	5,54€
	10	5,03€
	50	4,71€

Continued on next page >>

G503506L

DC Led Power Supply MINI-6-250mA 6W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CB



(LVD)

Weight: 45 Grams

Packging: Box 1 Unit

NOTES

ECO ERP Design. Constant current output 250mA

OTHER FEATURES

Length (mm): 53

Width (mm): 27

High (mm): 21

Colour: White

Voltage In (Vac): 220~240

Voltage Out (Vdc): 12~24

Intensidad Out (A): 0.25

Frecuency (Hz): 50~60

Power (W): 6

Room Temperature (°C): -20~+60

Critical Temperature (°C): 85

Ingress Protection: IP65

Dimmable: NO

Power factor: 0.6

DOCUMENTS

 [Data Sheet](#)

 [DC Led Power Supply MINI-6-250mA 6W](#)

 [CB](#)

 [Electromagnetic Compatibility TUV](#)

 [EMC TUV CERTIFIED](#)

 [LVD \(DIRECTA BAJO VOLTAJE\)](#)