

G503603A

**Led Power Supply CC Miniu-3.6-500 500mA 3.6W IP20**

April 04th, 2025, 13:10



## DESCRIPTION

Led power supply to incorporate with 500mA constant current output. Universal input voltage 100-240Vac. Output voltage from 2.5 to 7Vdc. Power range from 1.25 to 3.5W. Primary wiring with 18cm VDE 7726 0.5mm<sup>2</sup> cable and secondary wiring with 18cm UL1007 18AWG cable. Class II. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure.

## PRICE

	Lot	P.V.P. excluding VAT
	1	6,10€
	5	5,54€
	10	5,03€
	50	4,71€



Continued on next page >>

G503603A

Led Power Supply CC Miniu-3.6-500 500mA 3.6W IP20

## TECHNICAL SPECIFICATIONS

---

### SYMBOLS



**SELV**



**CB**



**UK  
CA**

Weight: 48 Grams

Packging: Box 1 Unit

### NOTES

---

ECO ERP Design. IP20. Constant current output 500mA.

### OTHER FEATURES

---

Length (mm): 53

Width (mm): 27

High (mm): 21

Colour: White

Voltage In (Vac): 100~240

Voltage Out (Vdc): 2.5~7

Intensidad Out (A): 0.5

Frecuency (Hz): 50~60

Power (W): 1.25~3.5

Room Temperature (°C): -20~+50

Critical Temperature (°C): 80

Life (Hours): 50000

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.50

### DOCUMENTS

---

 [Data Sheet](#)

 [Led Power Supply CC Miniu-3.6-500 500mA 3.6W IP20](#)

 [CB](#)

 [EMC TUV CERTIFIED](#)

 [Safety TUV CERTIFIED](#)