

G503715B

DC Led Power Supply MIW-15 multi-corriente up to 700mA 15W

December 04th, 2024, 09:15



DESCRIPTION

Led power supply to incorporate with multi constant current output configurable with Dip-switch from 300mA (12-50Vdc) to 700mA (12-21Vdc). Wiring with 18cm cable in primary and secondary. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure.

PRICE

	Lot	P.V.P. excluding VAT
	1	8,79€
	5	7,98€
	10	7,25€
	50	6,77€



Continued on next page >>

G503715B

DC Led Power Supply MIW-15 multi-corriente up to 700mA 15W

TECHNICAL SPECIFICATIONS

SYMBOLS

SELV



CB



(EMC)



Weight: 65 Grams

NOTES

ECODesign ERP. To incorporate. Constant current output selectable from 300mA to 700mA by DIP switch.

OTHER FEATURES

Length (mm): 54

High (mm): 24

Voltage In (Vac): 100~277

Intensidad Out (A): 0.3~0.7

Power (W): 15

Critical Temperature (°C): 90

Ingress Protection: IP20

Width (mm): 40

Colour: White

Intensidad In (A): 0.2

Frecuency (Hz): 50~60

Room Temperature (°C): -20~+50

Life (Hours): 50000

Power factor: 0.90

DOCUMENTS

 [Data Sheet](#)

 [DC Led Power Supply MIW-15 multi-corriente up to 700mA 15W](#)

 [NEMKO \(Norway\)](#)