

G503725C

Power supply Led multicourant variable DALI DC EUM-25D 700mA 25W

March 10th, 2025, 00:06



DESCRIPTION

Dimmable LED driver for stand-alone use certified DALI-2 DT6 (incl. Parts 251, 252,253) with multi-current output configurable with Dip-switch from 260mA (10-42Vdc) to 700mA (10-38Vdc). Regulation range 0.1-100%. Automatic contacts. Screwless snap-on covers. DALI and PUSH dimmable. ON-OFF corridor function and dimming with motion sensor. Class II. Protection against open circuit, short circuit, overload and over temperature. Automatic reset in case of failure.

PRICE

Lot	P.V.P. excluding VAT
1	25,35€
5	23,04€
10	20,94€
50	19,58€

Continued on next page >>

G503725C

Power supply Led multicourant variable DALI DC EUM-25D 700mA 25W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CB



(EMC)



**UK
CA**



Weight: 145 Grams

NOTES

ECO ERP Design. Constant multi-current output from 260mA to 700mA. Dimmable DALI DT6

OTHER FEATURES

Length (mm): 137

Width (mm): 44

High (mm): 22

Colour: White

Voltage In (Vac): 220~240

Voltage Out (Vdc): 10~42

Intensidad Out (A): 0.26~0.7

Frecuency (Hz): 50~60

Power (W): 10.9~26.6

Room Temperature (°C): -20~+45

Critical Temperature (°C): 90

Life (Hours): 50000

Ingress Protection: IP20

Dimmable: Push&DALI

Power factor: 0.95

DOCUMENTS

[Data Sheet](#)

[Power supply Led multicourant variable DALI DC EUM-25D 700mA 25W](#)

[CB](#)

[CE](#)