

G503712B

Power supply Led multicourant variable DALI DC MIM-12D 700mA 12W

March 09th, 2025, 16:51



DESCRIPTION

Dimmable Led power supply to incorporate DALI-2 certificate (incl. Parts 251, 252,253) with multi constant current output configurable with Dip-switch from 100mA (2-42Vdc) to 700mA (2-18Vdc). Regulation range 0.1-100%. Wiring with 18cm cable in primary, secondary and DALI. Dimmable by DALI and PUSH. ON-OFF hallway function and dimming with motion sensor. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure.

PRICE

	Lot	P.V.P. excluding VAT
	1	21,05€
	5	19,14€
	10	17,39€
	50	16,25€



Continued on next page >>

G503712B

Power supply Led multicourant variable DALI DC MIM-12D 700mA 12W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV

CB



UK
CA



Weight: 9 Grams

NOTES

ECO ERP Design. Constant multi-current output from 100mA to 700mA. Dimmable DALI and PUSH

OTHER FEATURES

Length (mm): 65

Width (mm): 43

High (mm): 24

Colour: White

Voltage In (Vac): 220~240

Voltage Out (Vdc): 2~42

Intensidad Out (A): 0.1~0.7

Frecuency (Hz): 50~60

Power (W): 4.2~12.6

Room Temperature (°C): -20~+60

Critical Temperature (°C): 90

Life (Hours): 50000

Ingress Protection: IP20

Dimmable: Push&DALI

Power factor: 0.95

DOCUMENTS

 [Data Sheet](#)

 [Power supply Led multicourant variable DALI DC MIM-12D 700mA 12W](#)

 [CB](#)

 [CE](#)

 [NEMKO \(Norway\)](#)