

G503840A

Dimmable DALI DC MIM-30D multicurrent Led power supply 1200mA40W

March 10th, 2025, 00:04



DESCRIPTION

Dimmable Led power supply to incorporate DALI-2 certificate (incl. Parts 251, 252,253) with multi constant current output configurable with Dip-switch from 700mA (10-42Vdc) to 1200mA (10-33Vdc). Regulation range 0.1-100%. Wiring with 18cm cable in primary, secondary and DALI. Dimmable by DALI and PUSH. ON-OFF hallway function and dimming with motion sensor. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure.

PRICE

Lot	P.V.P. excluding VAT
1	26,07€
5	23,70€
10	21,54€
50	20,14€



G503840A

Dimmable DALI DC MIM-30D multicurrent Led power supply 1200mA40W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV

CB



**UK
CA**



Weight: 211 Grams

NOTES

ECO ERP Design. Constant multi-current output from 700mA to 1200mA. Dimmable DALI and PUSH

OTHER FEATURES

Length (mm): 93

Width (mm): 55

High (mm): 32

Colour: White

Voltage In (Vac): 220~240

Intensidad Out (A): 0.7~1.2

Frecuency (Hz): 50~60

Power (W): 29.4~40

Room Temperature (°C): -20~+60

Critical Temperature (°C): 90

Life (Hours): 50000

Ingress Protection: IP20

Dimmable: Push&DALI

Power factor: 0.95

DOCUMENTS

[Data Sheet](#)



[CB](#)

[CE](#)

[NEMKO \(Norway\)](#)