

G503706K

Dimmable DC Led Power Supply Mini-6-700T 700mA 6W IP65

January 07th, 2025, 02:45



DESCRIPTION

IP65 Led power supply to incorporate with 700mA constant current output. Output voltage from 4 to 9 Vdc. Power range from 2.8 to 6W. Wiring 18cm. in primary VDE 7726 0.5mm² and secondary UL1015 22AWG. Class II. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure.

PRICE

Lot	P.V.P. excluding VAT
1	9,20€
5	8,37€
10	7,61€
50	7,11€



Continued on next page >>

G503706K

Dimmable DC Led Power Supply Mini-6-700T 700mA 6W IP65

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CB



**UK
CA**

Weight: 40 Grams

NOTES

ECO ERP Design. IP65. Constant current output 700mA. Adjustable cut start or end of phase

OTHER FEATURES

Length (mm): 48

High (mm): 20

Voltage In (Vac): 220~240

Intensidad Out (A): 0.7

Power (W): 3~6

Critical Temperature (°C): 85

Ingress Protection: IP65

Power factor: 0.90

Width (mm): 30

Colour: White

Voltage Out (Vdc): 4~9

Frecuency (Hz): 50~60

Room Temperature (°C): -20~+60

Life (Hours): 50000

Dimmable: Corte inicio o fin de fase

DOCUMENTS

 [Data Sheet](#)

 [Dimmable DC Led Power Supply Mini-6-700T 700mA 6W IP65](#)

 [CB](#)

 [CE](#)

 [ENEC \(Norway\)](#)

 [NEMKO \(Norway\)](#)