

G503704

**Dimmable DC Mini-4-700T 700mA 4W IP65 Led Power Supply**

January 07th, 2025, 02:53



**DESCRIPTION**

IP65 Led power supply to incorporate with 700mA constant current output. Output voltage from 2.5 to 6 Vdc. Power range from 1.75 to 4.2W. Wiring 18cm. in primary VDE 7726 0.5mm<sup>2</sup> and secondary UL1015 22AWG. Class II. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure.

**PRICE**

Lot	P.V.P. excluding VAT
1	12,09€
5	10,08€
10	9,17€
50	8,71€



Continued on next page >>

G503704

## Dimmable DC Mini-4-700T 700mA 4W IP65 Led Power Supply

### TECHNICAL SPECIFICATIONS

#### SYMBOLS



**SELV**



**CB**



**UK  
CA**

Weight: 40 Grams

#### NOTES

ECO ERP Design. IP65. Constant current output 700mA. Adjustable cut start or end of phase

#### OTHER FEATURES

Length (mm): 48

High (mm): 20

Voltage In (V): 220~240

Intensidad Out (A): 0.7

Power (W): 2~4

Critical Temperature (°C): 85

Ingress Protection: IP65

Power factor: 0.90

Width (mm): 30

Colour: White

Voltage Out (Vdc): 2.5~6

Frecuency (Hz): 50~60

Room Temperature (°C): -20~+60

Life (Hours): 50000

Dimmable: Corte inicio o fin de fase

#### DOCUMENTS

[Data Sheet](#)

[Dimmable DC Mini-4-700T 700mA 4W IP65 Led Power Supply](#)

[CB](#)

[CE](#)

[ENEC \(Norway\)](#)

[NEMKO \(Norway\)](#)