

G503720B

Dimmable LED power supply DALI CC MIM-20D multi-corriente 700mA 20W

March 09th, 2025, 17:18



DESCRIPTION

Dimmable LED power supply to incorporate DALI-2 certified (incl. Parts 251, 252,253) with constant multi-current output configurable with Dip-switch from 300mA (2-42Vdc) to 700mA (2-28Vdc). Regulation range 0.1-100%. Wiring with 18cm cable in primary, secondary and DALI. Dimmable by DALI and by PUSH. ON-OFF corridor function and dimming with motion sensor. Protection against open circuit, short circuit, overload and over temperature. Automatic reset in case of failure.

PRICE

Lot	P.V.P. excluding VAT
1	22,58€
5	20,53€
10	18,66€
50	17,43€



G503720B

Dimmable LED power supply DALI CC MIM-20D multi-corriente 700mA 20W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV

CB



**UK
CA**



Weight: 118 Grams

NOTES

ECO ERP Design. Constant multi-current output from 300mA to 700mA. Dimmable DALI and PUSH

OTHER FEATURES

Length (mm): 85

High (mm): 23

Voltage In (Vac): 220~240

Frecuency (Hz): 50~60

Room Temperature (°C): -20~+60

Life (Hours): 50000

Dimmable: Push&DALI

Width (mm): 43

Colour: White

Intensidad Out (A): 0.3~0.7

Power (W): 12.6~20

Critical Temperature (°C): 90

Ingress Protection: IP20

Power factor: 0.95

DOCUMENTS

 [Data Sheet](#)



 [CB](#)

 [CE](#)

 [NEMKO \(Norway\)](#)