

 ${\tt LED\ TECHNOLOGY>Flexible\ Led\ Strips\ and\ accessories>Flexible\ Led\ Strips\ IP62-IP63}$   ${\tt Flexible\ Led\ Strips\ IP62-IP63\ 24V}$ 

### LFD524061A

# Flexible Led strip 5m IP65 24V 72W 3000K Warm white

April 05th, 2025, 12:00



## **DESCRIPTION**

Flexible LED strip at constant voltage D5050 60leds / m 24VDC 72W warm white 3000K. Supply voltage (Vdc) 24V. Total maximum current (A) 3. Power 14.4W / m; total 72W. Luminosity 1104Lm / meter; total 5520Lm. Total length 5 meters. Total number of LEDs 300. Divisible into modules of 6 LEDs every 10cm (one LED every 16.7mm). Degree of protection IP62 for humid environments with transparent epoxy coating. Adhesive application on the back. Parallel connection. White PCB color.

#### **PRICE**

Lot	P.V.P. excluding VAT
1	48,75€
5	44,25€
10	42,15€



Continued on next page >>



LED TECHNOLOGY > Flexible Led Strips and accessories > Flexible Led Strips IP62-IP63 Flexible Led Strips IP62-IP63 24V

### LFD524061A

## Flexible Led strip 5m IP65 24V 72W 3000K Warm white

### **TECHNICAL SPECIFICATIONS**

## SYMBOLS CERTIFICADOS



















Weight: 235 Grams Packging: Roll 5 Meters

# **NOTES**

Total number of led 300. Divisible in modules of 6 every 10cm, (one LED each 16.6mm). With adhesive. CRI> 80

#### **OTHER FEATURES**

Length (mm): 5000 Width (mm): 9

High (mm): 3 Colour: White PCB

Voltage In (Vdc): 24 Intensidad In (A): 3

Power (W/m): 14.4 Temperature (°C): -20+50

Room Temperature (°C): -20~+50 Colour Temperature (°K): 3000

Lumen/meter: 1104 Angle (º): 120

CRI (≥): 80 Life (Hours): 50000

Ingress Protection: IP62 Dimmable: SI

## **DOCUMENTS**

