

 ${\tt LED\ TECHNOLOGY>Flexible\ Led\ Strips\ and\ accessories>Flexible\ Led\ Strips\ IP62-IP63}$ ${\tt Flexible\ Led\ Strips\ IP62-IP63\ 24V}$

LFD524062

Flexible Led strip 5m IP65 24V 72W 4000K Neutral white

April 05th, 2025, 16:41



DESCRIPTION

Flexible LED strip at constant voltage D5050 60leds / m 24VDC 72W neutral white 4000K. Supply voltage (Vdc) 24V. Total maximum current (A) 3. Power 14.4W / m; total 72W. Luminosity 1175Lm / meter; total 5875Lm. Total length 5 meters. Total number of LEDs 300. Divisible into modules of 6 LEDs every 10cm (one LED every 16.7mm). Degree of protection IP62 for humid environments with transparent epoxy coating. Adhesive application on the back. Parallel connection. White PCB color.

PRICE

Lot	P.V.P. excluding VAT
1	48,75€
5	44,25€
10	42,15€

Continued on next page >>



 $\mbox{LED TECHNOLOGY} > \mbox{Flexible Led Strips and accessories} > \mbox{Flexible Led Strips IP62-IP63} \\ \mbox{Flexible Led Strips IP62-IP63} \\ \mbox{24V}$

LFD524062

Flexible Led strip 5m IP65 24V 72W 4000K Neutral white

TECHNICAL SPECIFICATIONS

SYMBOLS CERTIFICADOS



















Weight: 235 Grams Packging: Roll 5 Meters

NOTES

Total number of led 300. Divisible in modules of 3 every 5cm, (one LED each 16.6mm). With adhesive. CRI> 80

OTHER FEATURES

Length (mm): 5000 Width (mm): 9

High (mm): 3 Colour: White PCB Voltage In (Vdc): 24 Intensidad In (A): 3

Power (W/m): 14.4 Temperature (°C): -20+50

Room Temperature (°C): -20~+50 Colour Temperature (°K): 4000

Lumen/meter: 1175 Angle ($^{\circ}$): 120

CRI (≥): 80 Life (Hours): 50000

Ingress Protection: IP62 Dimmable: SI

DOCUMENTS



