

 ${\tt LED\ TECHNOLOGY>Flexible\ Led\ Strips\ and\ accessories>Flexible\ Led\ Strips\ IP62-IP63}$ ${\tt Flexible\ Led\ Strips\ IP62-IP63\ 24V}$

LFD224142

Flexible Led strip5m SMD2835-180led/m. IP62 24V 14,4W/m - 72W 2700K

April 05th, 2025, 08:46



DESCRIPTION

Flexible constant voltage LED strip D2835 180leds / m 24VDC 72W warm white 2700K. Supply voltage (Vdc) 24V. Total maximum current (A) 3. Power 14.4W / m; total 72W. Luminosity 1130Lm / meter; total 5650Lm. Total length 5 meters. Total number of LEDs 900. Divisible into modules of 6 LEDs every 5cm (one LED every 8.3mm). Degree of protection IP62 for humid environments. Adhesive application on the back. Parallel connection. White PCB color.

PRICE

Lot	P.V.P. excluding VAT
1	57,46€
5	52,26€
10	49,73€



Continued on next page >>



 ${\tt LED\ TECHNOLOGY > Flexible\ Led\ Strips\ and\ accessories > Flexible\ Led\ Strips\ IP62-IP63}}$ ${\tt Flexible\ Led\ Strips\ IP62-IP63\ 24V}$

LFD224142

Flexible Led strip5m SMD2835-180led/m. IP62 24V 14,4W/m - 72W 2700K

TECHNICAL SPECIFICATIONS

SYMBOLS CERTIFICADOS

















Weight: 204 Grams Packging: Roll 5 Meters

NOTES

Total number of led 900. Divisible in modules of 6 Led each 3,3cm, (one led every 5,6mm). With adhesive

OTHER FEATURES

Length (mm): 5000 Width (mm): 10

High (mm): 3 Colour: White PCB Voltage In (Vdc): 24 Intensidad In (A): 2

Power (W/m): 14.4 Temperature (°C): -20+50

Room Temperature (°C): -20~+50 Colour Temperature (°K): 2700

Lumen/meter: 1130 Angle (°): 120

CRI (≥): 80 Life (Hours): 50000

Ingress Protection: IP62 Dimmable: SI

DOCUMENTS

Data Sheet

L CE

UR (USA)