

 ${\tt LED\ TECHNOLOGY>Flexible\ Led\ Strips\ and\ accessories>Flexible\ Led\ Strips\ IP62-IP63}$ ${\tt Flexible\ Led\ Strips\ IP62-IP63\ 24V}$

LFD224144

Flexible Led strip5m SMD2835-180led/m. IP62 24V 14,4W/m - 72W 4000K

January 22nd, 2025, 00:54



DESCRIPTION

Flexible LED strip at constant voltage D2835 180leds / m 24VDC 72W neutral white 4000K. Supply voltage (Vdc) 24V. Total maximum current (A) 3. Power 14.4W / m; total 72W. Luminosity 1224Lm / meter; total 6120Lm. Total length 5 meters. Total number of LEDs 900. Divisible into modules of 6 LEDs every 5cm (one LED every 8.3mm). Degree of protection IP62 for humid environments. Adhesive application on the back. Parallel connection. White PCB color.

PRICE

Lot	P.V.P. excluding VAT
1	57,46€
5	52,26€
10	49,73€



Continued on next page >>



 ${\tt LED\ TECHNOLOGY>Flexible\ Led\ Strips\ and\ accessories>Flexible\ Led\ Strips\ IP62-IP63}$ Flexible\ Led\ Strips\ IP62-IP63\ 24V}

LFD224144

Flexible Led strip5m SMD2835-180led/m. IP62 24V 14,4W/m - 72W 4000K

TECHNICAL SPECIFICATIONS

SYMBOLS CERTIFICADOS

















Weight: 204 Grams Packging: Roll 5 Meters

NOTES

Total number of led 900. Divisible in modules of 6 Led each 3,3cm, (one led every 5,6mm). With adhesive

OTHER FEATURES

Length (mm): 5000 Width (mm): 10

High (mm): 3 Colour: White PCB Voltage In (Vdc): 24 Intensidad In (A): 2

Power (W/m): 14.4 Temperature (°C): -20+50

Room Temperature (°C): -20~+50 Colour Temperature (°K): 4000

Lumen/meter: 1224 Angle ($^{\circ}$): 120

CRI (≥): 80 Life (Hours): 50000

Ingress Protection: IP62 Dimmable: SI

DOCUMENTS

Data Sheet

L CE

UR (USA)