

ELECTRICAL EQUIPMENT > Korner IP68 Connectors > IP68 Screw derivations
Derivations with screw IP68 cable section 2.5mm2 24A -400V

498M20T4 - 4533400

IP68 OK-M20T 4 pole 2.5mm2 screw-on branch connector

April 04th, 2025, 04:50



DESCRIPTION

4-pole connector. Black PA6.6 polyamide. Self-extinguishing UL.94V0-GWIT775°C. Operating temperature T105°C. Nickel-plated OT58 brass terminals, galvanized steel screws and silicone gasket.

PRICE

	Lot	P.V.P. excluding VAT
	1	9,14€
	5	7,31€
	25	6,97€
	75	6,64€

Continued on next page >>

498M20T4 - 4533400

IP68 OK-M20T 4 pole 2.5mm² screw-on branch connector

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS



Weight: 70 Grams

NOTES

Cable section 2.5mm²- 24A-400V and AWG14-15A-300V

OTHER FEATURES

Length (mm): 68

Width (mm): 104

Section (mm²): 2,5

Colour: Black

Voltage In (Vac): 400

Intensidad In (A): 24

Temperature (°C): 105

Ingress Protection: IP68

DOCUMENTS

 [Data Sheet](#)

 [C UR U.S. \(USA-Canada\)](#)

 [Electromagnetic compatibility TÜV SÜD](#)