

LUE57129402F2

Led Cob EDC / 57C / 12W / 940 / 230V / F201

December 22nd, 2024, 03:58



DESCRIPTION

Led module COB series F2 direct to mains. Dimmable with leading and trailing edge dimmers. Efficiency > 0.95. THD < 30%. Mounting holes according to Zhaga standard. Complying SLR. SVM < 0.1. Pst < 0.4. Flicker free.

PRICE

| | Lot | P.V.P. excluding VAT |
|--|-----|----------------------|
| | 1 | 15,68€ |
| | 5 | 13,07€ |
| | 50 | 11,88€ |
| | 100 | 11,31€ |

Continued on next page >>

LUE57129402F2

Led Cob EDC / 57C / 12W / 940 / 230V / F201

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS



(EMC)

(LVD)

Weight: 8 Grams

NOTES

ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard

OTHER FEATURES

| | |
|--------------------------------------|-------------------------------|
| High (mm): 7,6 | Diameter (mm): 57 |
| Voltage In (Vac): 230 | Frecuency (Hz): 50~60 |
| Power (W): 12 | Temperature (°C): -40+85 |
| Room Temperature (°C): -40~+85 | Critical Temperature (°C): 85 |
| Colour Temperature (°K): 4000 | Lumen: 1127 |
| Angle (°): 120 | Energy efficiency: F |
| CRI (≥): 90 | Life (Hours): 50000 |
| Dimmable: Corte inicio o fin de fase | Power factor: >0,95 |

DOCUMENTS

 [Data Sheet](#)

 [EPREL Datasheet](#)

 [Led Cob EDC / 57C / 12W / 940 / 230V / F201](#)

 [Electromagnetic compatibility](#)

 [LVD \(DIRECTA BAJO VOLTAJE\)](#)