

LUE57208302D

Led Cob EDC/57C/20W/830DW/230V/A/FF Dimable to warm and FF

February 01st, 2025, 19:41



DESCRIPTION

Direct COB Led module to mains. Minimum Flicker. Dimmable to warm with most leading or trailing edge diimers. 120V (UL) and 230V (CE) version. By decreasing the light intensity, the color temperature decreases from 3000K to 1800K. Circuit with temperature protection at 150°C and overvoltage.

PRICE

	Lot	P.V.P. excluding VAT
	1	20,44€
	5	17,03€
	50	14,17€
	100	13,52€

Continued on next page >>

LUE57208302D

Led Cob EDC/57C/20W/830DW/230V/A/FF Dimable to warm and FF

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS



Weight: 14 Grams

Packging: Box 100 Units

NOTES

Automatic connectors. Dimmable with most Triac dimmers. SDCM 3. Mounting holes Zhaga standards.

OTHER FEATURES

High (mm): 4,8

Voltage In (Vac): 230

Frecuency (Hz): 50~60

Temperature (°C): -40+85

Critical Temperature (°C): 85

Lumen: 2000

Energy efficiency: A+

Life (Hours): 50000

Power factor: >0.99

Diameter (mm): 57

Intensidad In (A): 0.087

Power (W): 20

Room Temperature (°C): -40~+85

Colour Temperature (°K): 1800~3000

Angle (°): 120

CRI (≥): 80

Dimmable: Corte inicio o fin de fase

DOCUMENTS

 [Data Sheet](#)