

GTC21500 - 122291

Led Driver CC ECO 21-500 500mA 21W

November 23rd, 2024, 10:26



DESCRIPTION

Led power supply for independent use at constant current 500mA. The output voltage is from 32 to 42V and the power range is from 16 to 21W. Class II. Protection against open circuit, short circuit, over load and over temperature. Efficiency > 84%. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI code 122291

PRICE

Lot	P.V.P. excluding VAT
1	6,90€
5	6,28€
10	5,71€
50	5,28€



Continued on next page >>

GTC21500 - 122291

Led Driver CC ECO 21-500 500mA 21W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CERTIFICADOS

CB



CE



**UK
CA**

Weight: 115 Grams

NOTES

ECO ERP Directives. 500mA constant current power supply.

OTHER FEATURES

Length (mm): 115

High (mm): 29

Voltage Out (Vdc): 32~42

Frecuency (Hz): 50~60

Room Temperature (°C): 0~+50

Ingress Protection: IP20

Power factor: 0.9

Width (mm): 45

Voltage In (Vac): 220~240

Intensidad Out (A): 0.5

Power (W): 16~21

Critical Temperature (°C): 75

Dimmable: NO

DOCUMENTS

 [Data Sheet](#)

 [Led Driver CC ECO 21-500 500mA 21W](#)

 [CB](#)

 [CCC \(China\)](#)

 [CE](#)

 [ENEC \(Netherlands\)](#)

 [Regulatory Compliance Mark for Australia](#)

 [UKCA](#)