

GTC32700 - 122293

Led Driver CC ECO 32-700-750mA 32W

April 04th, 2025, 05:42



DESCRIPTION

Led power supply for independent use at constant current 700-750mA. The output voltage ranges from 30 to 42V and the power range is from 21 to 29.4-32W. Class II. Protection against open circuit, short circuit, over load and over temperature. Efficiency > 88%. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI Code 122293

PRICE

	Lot	P.V.P. excluding VAT
	1	10,96€
	5	9,97€
	10	9,06€
	40	8,39€



Continued on next page >>

GTC32700 - 122293

Led Driver CC ECO 32-700-750mA 32W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CERTIFICADOS

CB



CE



**UK
CA**

Weight: 140 Grams

NOTES

ECO ERP Directives. 700-750mA constant current power supply.

OTHER FEATURES

Length (mm): 108

High (mm): 32

Voltage Out (Vdc): 30~42

Frecuency (Hz): 50~60

Room Temperature (°C): 0~+50

Ingress Protection: IP20

Power factor: 0.92

Width (mm): 68

Voltage In (Vac): 220~240

Intensidad Out (A): 0.7~0.75

Power (W): 21~32

Critical Temperature (°C): 80

Dimmable: NO

DOCUMENTS

 [Data Sheet](#)

 [Led Driver CC ECO 32-700-750mA 32W](#)

 [CB](#)

 [CCC \(China\)](#)

 [CE](#)

 [ENEC \(Netherlands\)](#)

 [Regulatory Compliance Mark for Australia](#)

 [UKCA](#)