

GTC20500 - 127032

Led Driver CC MINI MD 500mA 20W

January 07th, 2025, 03:09



DESCRIPTION

Led power supply for independent use at constant current 500mA. The output voltage ranges from 16 to 42V and the power range is from 8 to 21W. Class II. Dimmable by leading edge (Triac) or trailing edge (IGBT) dimmers. Protection against open circuit, short circuit, over load and over temperature. Efficiency > 89%. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI Code 127032

PRICE

| Lot | P.V.P. excluding VAT |
|-----|----------------------|
| 1 | 17,34€ |
| 5 | 15,76€ |
| 10 | 14,33€ |
| 50 | 13,27€ |



Continued on next page >>

GTC20500 - 127032

Led Driver CC MINI MD 500mA 20W

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS

CB



EAC



UK
CA

Weight: 108 Grams

NOTES

ECO ERP directives. 500mA constant current output power supply. Dimmable leading and trailing edge dimmers.

OTHER FEATURES

Length (mm): 111

Width (mm): 52

High (mm): 22

Voltage In (Vac): 220~240

Voltage Out (Vdc): 16~42

Intensidad Out (A): 0.5

Frecuency (Hz): 50~60

Power (W): 20

Room Temperature (°C): -25~+45

Critical Temperature (°C): 75

Ingress Protection: IP20

Dimmable: Corte inicio o fin de fase

Power factor: 0.95

DOCUMENTS

 [Data Sheet](#)

 [Led Driver CC MINI MD 500mA 20W](#)

 [CB](#)

 [CCC \(China\)](#)

 [CE](#)

 [EAC \(RUSIA\)](#)

 [ENEC \(Netherlands\)](#)

 [Regulatory Compliance Mark for Australia](#)

 [UKCA](#)