

GTC2070B - 127034

Led Driver CC MINI MD 700mA 20W

January 07th, 2025, 02:52



DESCRIPTION

Led power supply for independent use at constant current 700mA. The output voltage ranges from 16 to 28V and the power range is from 11,2 to 19,6W. Class II. Dimmable by leading edge (Triac) or trailing edge (IGBT) dimmers. Protection against open circuit, short circuit, over load and over temperature. Efficiency > 89%. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI Code 127034

PRICE

Lot	P.V.P. excluding VAT
1	17,00€
5	15,46€
10	14,05€
50	13,01€



Continued on next page >>

GTC2070B - 127034

Led Driver CC MINI MD 700mA 20W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CERTIFICADOS

CB



EAC



**UK
CA**

Weight: 108 Grams

NOTES

ECO ERP directives. 700mA constant current output power supply. Dimmable leading and trailing edge dimmers.

OTHER FEATURES

Length (mm): 115

High (mm): 22

Voltage Out (Vdc): 16~28

Frecuency (Hz): 50~60

Room Temperature (°C): -25~+45

Ingress Protection: IP20

Power factor: 0.95

Width (mm): 52

Voltage In (Vac): 220~240

Intensidad Out (A): 0.7

Power (W): 11.2~19.6

Critical Temperature (°C): 75

Dimmable: Corte inicio o fin de fase

DOCUMENTS

[Data Sheet](#)

[Led Driver CC MINI MD 700mA 20W](#)

[CB](#)

[CCC \(China\)](#)

[CE](#)

[EAC \(RUSIA\)](#)

[ENEC \(Netherlands\)](#)

[Regulatory Compliance Mark for Australia](#)

[UKCA](#)