

GTC15360 - 127710

Led Driver CC MP 15 HPFU multi-current up to 360mA 15W

March 09th, 2025, 16:52



DESCRIPTION

Led power supply for independent use with constant multi-current output selectable by DIP switch. Output voltage range 2-41.5V High efficiency 85%. Class II. Output current from 60mA to 360mA. Protection against open circuit, short circuit, over load and over temperature. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI COde 127710

PRICE

Lot	P.V.P. excluding VAT
1	18,27€
5	16,60€
10	15,09€
50	13,98€

Continued on next page >>

GTC15360 - 127710

Led Driver CC MP 15 HPFU multi-current up to 360mA 15W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CB



EAC



**UK
CA**

Weight: 17 Grams

NOTES

ECO ERP Directives. Selectable output current from 60mA to 360mA by DIP-SWITCH.

OTHER FEATURES

Length (mm): 115

Width (mm): 34

High (mm): 19

Voltage In (Vac): 100~240

Voltage Out (Vdc): 2~41.5

Intensidad Out (A): 0.06~0.36

Frecuency (Hz): 50~60

Power (W): 0.12~15

Room Temperature (°C): -25~+45

Critical Temperature (°C): 75

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.8

DOCUMENTS

 [Data Sheet](#)

 [Led Driver CC MP 15 HPFU multi-current up to 360mA 15W](#)

 [CB](#)

 [CE](#)

 [C UR U.S. \(USA-Canada\)](#)

 [EAC \(RUSIA\)](#)

 [ENEC \(Netherlands\)](#)

 [Regulatory Compliance Mark for Australia](#)

 [UKCA](#)