

GTC55350 - 127524

Led Driver CC MPSE 55-350 multicurrent up to 350mA 55W

January 07th, 2025, 02:21



DESCRIPTION

Led power supply Linear for built-in use with constant multi-current output selectable by DIP switch. High efficiency 94%. Output current from 100mA to 350mA. Protection against open circuit, short circuit, over load and over temperature. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI Code 127524

PRICE

	Lot	P.V.P. excluding VAT
	1	15,18€
	5	13,79€
	10	12,55€
	70	11,61€

Continued on next page >>

GTC55350 - 127524

Led Driver CC MPSE 55-350 multicurrent up to 350mA 55W

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS

CB

CE

EAC



UK
CA

Weight: 140 Grams

Packging: Box 70 Unit

NOTES

ECO ERP Directives. DIP-SWITCH selectable output current from 100mA to 350mA

OTHER FEATURES

Length (mm): 237

Width (mm): 30

High (mm): 21

Voltage In (Vac): 220~240

Intensidad Out (A): 0.1~0.35

Frecuency (Hz): 50~60

Power (W): 7~55

Room Temperature (°C): -25~+50

Critical Temperature (°C): 85

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.95

DOCUMENTS

 [Data Sheet](#)

 [Led Driver CC MPSE 55-350 multicurrent up to 350mA 55W](#)

 [CB](#)

 [CE](#)

 [ENEC \(Netherlands\)](#)

 [Regulatory Compliance Mark for Australia](#)

 [UKCA](#)