

GTC22500 - 127570

Led Driver CC PROFLAT 22 Multicurrent up to 500mA 22W

March 09th, 2025, 17:04



DESCRIPTION

Led power supply for built-in use with constant multi-current output selectable by DIP switch. High efficiency 89%. Class II. Output current from 125mA to 500mA. Protection against open circuit, short circuit, over load and over temperature. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI Code 127570

PRICE

Lot	P.V.P. excluding VAT
1	11,27€
5	10,24€
10	9,31€
50	8,63€

Continued on next page >>

GTC22500 - 127570

Led Driver CC PROFLAT 22 Multicurrent up to 500mA 22W

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS

CB



EAC

(EMC)



UK
CA

Weight: 113 Grams

NOTES

ECO ERP Directives. DIP-SWITCH selectable output current from 125mA to 500mA

OTHER FEATURES

Length (mm): 146

Width (mm): 43

High (mm): 22

Voltage In (Vac): 220~240

Intensidad Out (A): 0.125~0.5

Frecuency (Hz): 50~60

Power (W): 3~22

Room Temperature (°C): -25~+45

Critical Temperature (°C): 75

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.9

DOCUMENTS

 [Data Sheet](#)

 [Led Driver CC PROFLAT 22 Multicurrent up to 500mA 22W](#)

 [CB](#)

 [CCC \(China\)](#)

 [CE](#)

 [EAC \(RUSIA\)](#)

 [Electromagnetic compatibility](#)

 [ENEC \(Netherlands\)](#)

 [Regulatory Compliance Mark for Australia](#)

 [UKCA](#)