

GTC32725 - 127572

Led Driver CC PROFLAT 30 Multicurrent up to 725mA 32W

March 09th, 2025, 16:54



DESCRIPTION

Led power supply for built-in use with constant multi-current output selectable by DIP switch. High efficiency 90%. Class II. Output current from 350mA to 725mA. Protection against open circuit, short circuit, over load and over temperature. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI Code 127572

PRICE

Lot	P.V.P. excluding VAT
1	14,61€
5	13,29€
10	12,08€
50	11,18€

Continued on next page >>

GTC32725 - 127572

Led Driver CC PROFLAT 30 Multicurrent up to 725mA 32W

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS

CB



CE

EAC

(EMC)



UK
CA

Weight: 113 Grams

NOTES

ECO ERP Directives. DIP-SWITCH selectable output current from 350mA to 725mA

OTHER FEATURES

Length (mm): 146

Width (mm): 43

High (mm): 22

Voltage In (Vac): 220~240

Intensidad Out (A): 0.35~0.725

Frecuency (Hz): 50~60

Power (W): 3~32

Room Temperature (°C): -25~+45

Critical Temperature (°C): 85

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.95

DOCUMENTS

 [Data Sheet](#)

 [Led Driver CC PROFLAT 30 Multicurrent up to 725mA 32W](#)

 [CB](#)

 [CCC \(China\)](#)

 [CE](#)

 [EAC \(RUSIA\)](#)

 [Electromagnetic compatibility](#)

 [ENEC \(Netherlands\)](#)

 [Regulatory Compliance Mark for Australia](#)

 [UKCA](#)