

GTC401050 - 127574

Led Driver CC PROFLAT 40 multi-current 1050mA 40W

November 03rd, 2024, 13:38



DESCRIPTION

Led power supply for built-in use with constant multi-current output selectable by DIP switch. High efficiency 90%. Class II. Output current from 300mA to 1050mA. Protection against open circuit, short circuit, over load and over temperature. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI Code 127574

PRICE

Lot	P.V.P. excluding VAT
1	17,71€
5	16,11€
10	14,64€
50	13,56€



Continued on next page >>

GTC401050 - 127574

Led Driver CC PROFLAT 40 multi-current 1050mA 40W

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS

CB



EAC

(EMC)



UK
CA

Weight: 113 Grams

NOTES

ECO ERP Directives. Output current selectable by DIP-SWITCH from 300mA to 1050mA

OTHER FEATURES

Length (mm): 146

High (mm): 22

Intensidad Out (A): 0.3~1.05

Power (W): 5~40

Critical Temperature (°C): 90

Dimmable: NO

Width (mm): 43

Voltage In (Vac): 220~240

Frecuency (Hz): 50~60

Room Temperature (°C): -25~+45

Ingress Protection: IP20

Power factor: 0.95

DOCUMENTS

 [Data Sheet](#)

 [Led Driver CC PROFLAT 40 multi-current 1050mA 40W](#)

 [CB](#)

 [CCC \(China\)](#)

 [CE](#)

 [EAC \(RUSIA\)](#)

 [Electromagnetic compatibility](#)

 [ENEC \(Netherlands\)](#)

 [Regulatory Compliance Mark for Australia](#)

 [UKCA](#)