

GTC401050 - 127574

**Led Driver CC PROFLAT 40 multi-current 1050mA 40W**

January 07th, 2025, 02:24



## DESCRIPTION

Led power supply for built-in use with constant multi-current output selectable by DIP switch. High efficiency 90%. Class II. Output current from 300mA to 1050mA. Protection against open circuit, short circuit, over load and over temperature. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI Code 127574

## PRICE

|  | Lot | P.V.P. excluding VAT |
|--|-----|----------------------|
|  | 1   | 17,71€               |
|  | 5   | 16,11€               |
|  | 10  | 14,64€               |
|  | 50  | 13,56€               |



Continued on next page >>

GTC401050 - 127574

**Led Driver CC PROFLAT 40 multi-current 1050mA 40W**

## TECHNICAL SPECIFICATIONS

---

### SYMBOLS



### CERTIFICADOS

CB



EAC

(EMC)



UK  
CA

Weight: 113 Grams

### NOTES

---

ECO ERP Directives. Output current selectable by DIP-SWITCH from 300mA to 1050mA

### OTHER FEATURES

---

Length (mm): 146

High (mm): 22

Intensidad Out (A): 0.3~1.05

Power (W): 5~40

Critical Temperature (°C): 90

Dimmable: NO

Width (mm): 43

Voltage In (Vac): 220~240

Frecuency (Hz): 50~60

Room Temperature (°C): -25~+45

Ingress Protection: IP20

Power factor: 0.95

### DOCUMENTS

---

 [Data Sheet](#)

 [Led Driver CC PROFLAT 40 multi-current 1050mA 40W](#)

 [CB](#)

 [CCC \(China\)](#)

 [CE](#)

 [EAC \(RUSIA\)](#)

 [Electromagnetic compatibility](#)

 [ENEC \(Netherlands\)](#)

 [Regulatory Compliance Mark for Australia](#)

 [UKCA](#)