

GTC401050 - 127574

**Led Driver CC PROFLAT 40 multi-current 1050mA 40W**

March 09th, 2025, 17:17



## DESCRIPTION

Led power supply for built-in use with constant multi-current output selectable by DIP switch. High efficiency 90%. Class II. Output current from 300mA to 1050mA. Protection against open circuit, short circuit, over load and over temperature. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI Code 127574

## PRICE

Lot	P.V.P. excluding VAT
1	17,71€
5	16,11€
10	14,64€
50	13,56€



Continued on next page >>

GTC401050 - 127574

**Led Driver CC PROFLAT 40 multi-current 1050mA 40W**

## TECHNICAL SPECIFICATIONS

---

### SYMBOLS



### CERTIFICADOS

CB



EAC

(EMC)



UK  
CA

Weight: 113 Grams

### NOTES

---

ECO ERP Directives. Output current selectable by DIP-SWITCH from 300mA to 1050mA

### OTHER FEATURES

---

Length (mm): 146

Width (mm): 43

High (mm): 22

Voltage In (Vac): 220~240

Intensidad Out (A): 0.3~1.05

Frecuency (Hz): 50~60

Power (W): 5~40

Room Temperature (°C): -25~+45

Critical Temperature (°C): 90

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.95

### DOCUMENTS

---

 [Data Sheet](#)

 [Led Driver CC PROFLAT 40 multi-current 1050mA 40W](#)

 [CB](#)

 [CCC \(China\)](#)

 [CE](#)

 [EAC \(RUSIA\)](#)

 [Electromagnetic compatibility](#)

 [ENEC \(Netherlands\)](#)

 [Regulatory Compliance Mark for Australia](#)

 [UKCA](#)