

GTC2090B - 122198

Led Driver CC UNIVERSALE 20HC multi-current 900mA 20W

December 04th, 2024, 09:15



DESCRIPTION

Led power supply for independent use with constant multi-current output and 24Vdc constant voltage selectable by DIP switch. High efficiency 87%. Class II. Output current from 350mA to 900mA. Protection against open circuit, short circuit, over load and over temperature. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI Code 122198

PRICE

Lot	P.V.P. excluding VAT
1	15,07€
5	13,68€
10	12,45€
50	11,53€



Continued on next page >>

GTC2090B - 122198

Led Driver CC UNIVERSALE 20HC multi-current 900mA 20W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CB



EAC



**UK
CA**

Weight: 108 Grams

NOTES

ECO ERP Directives. Output current selectable by DIP-SWITCH from 350mA to 900mA and at constant voltage 24Vdc

OTHER FEATURES

Length (mm): 111

Width (mm): 52

High (mm): 22

Voltage In (Vac): 110~240

Intensidad Out (A): 0.35~0.9

Frecuency (Hz): 50~60

Power (W): 1~20

Room Temperature (°C): -25~+50

Critical Temperature (°C): 75

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.93

DOCUMENTS

[Data Sheet](#)

[Led Driver CC UNIVERSALE 20HC multi-current 900mA 20W](#)

[CB](#)

[CE](#)

[C UR U.S. \(USA-Canada\)](#)

[EAC \(RUSIA\)](#)

[ENEC \(Netherlands\)](#)

[IRAM \(Argentina\)](#)

[Regulatory Compliance Mark for Australia](#)

[UKCA](#)