

GTC3270A - 125424

Led Driver CV CC DIM JOLLY DALI multi-current 700mA 32W

January 08th, 2025, 07:31



DESCRIPTION

DALI dimmable Led power supply for independent use with constant multi-current output and constant voltage 12 and 24Vdc selectable by DIP switch. High efficiency 87%. Class II. Output current from 250mA to 700mA. Protection against open circuit, short circuit, overload and over temperature. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI Code 125424

PRICE

Lot	P.V.P. excluding VAT
1	37,06€
5	33,70€
10	30,65€
50	28,37€



Continued on next page >>

GTC3270A - 125424

Led Driver CV CC DIM JOLLY DALI multi-current 700mA 32W

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS

CB



EAC



UK
CA

Weight: 135 Grams

NOTES

ECO ERP Directives. DALI dimmable. Output current selectable by DIP-SWITCH from 250mA to 700mA and at constant voltage 12 and 24Vdc

OTHER FEATURES

Length (mm): 103

Width (mm): 67

High (mm): 21

Voltage In (Vac): 110~240

Intensidad Out (A): 0.25~0.7

Frecuency (Hz): 50~60

Power (W): 1~32

Room Temperature (°C): -25~+50

Critical Temperature (°C): 75

Ingress Protection: IP20

Dimmable: DALI

Power factor: 0.95

DOCUMENTS

 [Data Sheet](#)

 [Led Driver CV CC DIM JOLLY DALI multi-current 700mA 32W](#)

 [CB](#)

 [CE](#)

 [C UR U.S. \(USA-Canada\)](#)

 [EAC \(RUSIA\)](#)

 [ENEC \(Netherlands\)](#)

 [IRAM \(Argentina\)](#)

Copyright © 2025 Koala Components, S.A. All rights reserved.

 [Regulatory Compliance Mark for Australia](#)

 [UKCA](#)