

GTC3290A - 122260

Led Driver CV CC DIM JOLLY MD multicurrent 900mA 32W

January 08th, 2025, 07:18



DESCRIPTION

Dimmable Led power supply by cutting start or end of phase. For independent use with constant multicurrent output selectable by DIP switch from 350mA to 750mA and a constant voltage selectable from 12Vdc, 24Vdc and 28Vdc in the 3 cases with fixed output intensity at 900mA. Class II. Protection against open circuit, short circuit, overload and over temperature. Warranty 7 years (3% failure rate) 10 years (5% failure rate). TCI code 122260

PRICE

	Lot	P.V.P. excluding VAT
	1	40,69€
	5	37,00€
	10	33,63€
	40	31,15€



Continued on next page >>

LED TECHNOLOGY > Electronic Led Power Supplies > LED Power Supplies Constant Current
Electronic Led power dimmable constant current

GTC3290A - 122260

Led Driver CV CC DIM JOLLY MD multicurrent 900mA 32W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CERTIFICADOS

CB



EAC

(EMC)



KEMA



UK
CA

Weight: 185 Grams

Packging: Box 40 Units

NOTES

ECO ERP Directives. DALI dimmable. Output current selectable by DIP-SWITCH from 350mA to 750mA

OTHER FEATURES

Length (mm): 166

Width (mm): 46

High (mm): 34

Voltage In (Vac): 220~240

Intensidad Out (A): 0.35~0.75

Frecuency (Hz): 50~60

Power (W): 0~32

Room Temperature (°C): -25~+45

Critical Temperature (°C): 75

Ingress Protection: IP20

Dimmable: Corte inicio o fin de fase

Power factor: 0.97

DOCUMENTS

[Data Sheet](#)

[Led Driver CV CC DIM JOLLY MD multicurrent 900mA 32W](#)

[CB](#)

[CCC \(China\)](#)

[CE](#)

[EAC \(RUSIA\)](#)

[Electromagnetic compatibility](#)

[ENEC \(Netherlands\)](#)

[Regulatory Compliance Mark for Australia](#)

[UKCA](#)