

GTC2070A - 125403

Led Driver CV CC DIM MINI JOLLY DALI multi-current 700mA 20W

March 09th, 2025, 16:58



DESCRIPTION

DALI dimmable Led power supply for independent use with constant multi-current output and constant voltage 24Vdc selectable by DIP switch. High efficiency 87%. Class II. Output current from 250mA to 700mA. Protection against open circuit, short circuit, overload and over temperature. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI Code 125403

PRICE

Lot	P.V.P. excluding VAT
1	34,57€
5	31,43€
10	28,57€
50	26,46€



Continued on next page >>

GTC2070A - 125403

Led Driver CV CC DIM MINI JOLLY DALI multi-current 700mA 20W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CERTIFICADOS

CB



EAC



**UK
CA**

Weight: 106 Grams

NOTES

ECO ERP Directives. DALI dimmable. Output current selectable by DIP-SWITCH from 250mA to 700mA and at constant voltage 24Vdc

OTHER FEATURES

Length (mm): 111

High (mm): 22

Intensidad Out (A): 0.25~0.7

Power (W): 1~20

Critical Temperature (°C): 75

Dimmable: DALI

Width (mm): 52

Voltage In (Vac): 110~240

Frecuency (Hz): 50~60

Room Temperature (°C): -25~+45

Ingress Protection: IP20

Power factor: 0.95

DOCUMENTS

[Data Sheet](#)

[Led Driver CV CC DIM MINI JOLLY DALI multi-current 700mA 20W](#)

[CB](#)

[CE](#)

[C UR U.S. \(USA-Canada\)](#)

[EAC \(RUSIA\)](#)

[ENEC \(Netherlands\)](#)

[Regulatory Compliance Mark for Australia](#) Copyright © 2015 Koala Components, S.A. All rights reserved.

[UKCA](#)