

GTC2090A - 127556

Led Driver CV CC DIM MINI JOLLY MD multi-current 900mA 20W

March 09th, 2025, 17:04



DESCRIPTION

Dimmable Led power supply leading edge (Triac) or trailing edge (IGBT) for independent use with constant multi-current output and constant voltage 12 and 24Vdc selectable by DIP switch. High efficiency 88%. Class II. Output current from 250mA to 900mA. Protection against open circuit, short circuit, over load and over temperature. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI Code 127556

PRICE

Lot	P.V.P. excluding VAT
1	24,91€
5	22,65€
10	20,58€
50	19,06€



Continued on next page >>

GTC2090A - 127556

Led Driver CV CC DIM MINI JOLLY MD multi-current 900mA 20W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CERTIFICADOS

CB

CE

EAC



**UK
CA**

Weight: 108 Grams

NOTES

ECO ERP Directives. Dimmable by leading or trailing edge phase cut. Output current selectable by DIP-SWITCH from 250mA to 900mA and at constant voltage 12 and 24Vdc

OTHER FEATURES

Length (mm): 111

Width (mm): 52

High (mm): 22

Voltage In (Vac): 220~240

Intensidad Out (A): 0.25~0.9

Frecuency (Hz): 50~60

Power (W): 3~20

Room Temperature (°C): -25~+45

Critical Temperature (°C): 75

Ingress Protection: IP20

Dimmable: Corte inicio o fin de fase

Power factor: 0.85

DOCUMENTS

 [Data Sheet](#)

 [Led Driver CV CC DIM MINI JOLLY MD multi-current 900mA 20W](#)

 [CB](#)

 [CE](#)

 [EAC \(RUSIA\)](#)

 [ENEC \(Netherlands\)](#)

 [Regulatory Compliance Mark for Australia](#)

 [UKCA](#)