

GTC20700 - 122201

Led Driver CV CC UNIVERSALE 20 multi-current up to 700mA 20W

January 07th, 2025, 02:34



DESCRIPTION

Led power supply for built-in use with constant multi-current output and 24Vdc constant voltage selectable by DIP switch. High efficiency 88%. Class II. Output current from 250mA to 700mA. Protection against open circuit, short circuit, overload and over temperature. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio).

PRICE

| Lot | P.V.P. excluding VAT |
|-----|----------------------|
| 1 | 17,71€ |
| 5 | 16,11€ |
| 10 | 14,64€ |
| 50 | 13,55€ |

Continued on next page >>

GTC20700 - 122201

Led Driver CV CC UNIVERSALE 20 multi-current up to 700mA 20W

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS

CB



EAC

(EMC)



UK
CA

Weight: 108 Grams

NOTES

ECO ERP Directives. Output current selectable by DIP-SWITCH from 250mA to 700mA and at constant voltage 24Vdc

OTHER FEATURES

Length (mm): 111

Width (mm): 52

High (mm): 22

Voltage In (Vac): 220~240

Intensidad Out (A): 0.25~0.7

Frecuency (Hz): 50~60

Power (W): 1~20

Room Temperature (°C): -25~+50

Critical Temperature (°C): 80

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.97

DOCUMENTS

[Data Sheet](#)

[Led Driver CV CC UNIVERSALE 20 multi-current up to 700mA 20W](#)

[CB](#)

[CCC \(China\)](#)

[CE](#)

[EAC \(RUSIA\)](#)

[Electromagnetic compatibility](#)

[ENEC \(Netherlands\)](#)

[IRAM \(Argentina\)](#)

[Regulatory Compliance Mark for Australia](#)

[UKCA](#)