

GTC20700 - 122201

Led Driver CV CC UNIVERSALE 20 multi-current up to 700mA 20W

December 04th, 2024, 09:07



DESCRIPTION

Led power supply for built-in use with constant multi-current output and 24Vdc constant voltage selectable by DIP switch. High efficiency 88%. Class II. Output current from 250mA to 700mA. Protection against open circuit, short circuit, overload and over temperature. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio).

PRICE

Lot	P.V.P. excluding VAT
1	17,71€
5	16,11€
10	14,64€
50	13,55€

Continued on next page >>

GTC20700 - 122201

Led Driver CV CC UNIVERSALE 20 multi-current up to 700mA 20W

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS

CB



EAC

(EMC)



UK
CA

Weight: 108 Grams

NOTES

ECO ERP Directives. Output current selectable by DIP-SWITCH from 250mA to 700mA and at constant voltage 24Vdc

OTHER FEATURES

Length (mm): 111

High (mm): 22

Intensidad Out (A): 0.25~0.7

Power (W): 1~20

Critical Temperature (°C): 80

Dimmable: NO

Width (mm): 52

Voltage In (Vac): 220~240

Frecuency (Hz): 50~60

Room Temperature (°C): -25~+50

Ingress Protection: IP20

Power factor: 0.97

DOCUMENTS

 [Data Sheet](#)

 [Led Driver CV CC UNIVERSALE 20 multi-current up to 700mA 20W](#)

 [CB](#)

 [CCC \(China\)](#)

 [CE](#)

 [EAC \(RUSIA\)](#)

 [Electromagnetic compatibility](#)

 [ENEC \(Netherlands\)](#)

 [IRAM \(Argentina\)](#)

 [Regulatory Compliance Mark for Australia](#)

 [UKCA](#)