

**GTC80500 - 122214I**

**Led Driver CC MP 80-500 SLIM multi-current up to 500mA 80W**

December 04th, 2024, 08:56



**DESCRIPTION**

Led Power supply Linear to incorporate with constant multi-current output selectable by DIP switch. High efficiency 93%. Output current from 350mA to 500mA. Protection against open circuit, short circuit, over load and over temperature. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI Code 122214I

**PRICE**

	Lot	P.V.P. excluding VAT
	1	16,30€
	5	14,82€
	10	13,48€
	72	12,48€

Continued on next page >>

GTC80500 - 122214I

**Led Driver CC MP 80-500 SLIM multi-current up to 500mA 80W**

## TECHNICAL SPECIFICATIONS

### SYMBOLS



### CERTIFICADOS

CB



EAC

(EMC)



UK  
CA

Weight: 140 Grams

### NOTES

ECO ERP Directives. DIP-SWITCH selectable output current from 350mA to 500mA

### OTHER FEATURES

Length (mm): 280

High (mm): 21

Intensidad Out (A): 0.35~0.5

Power (W): 10~80

Critical Temperature (°C): 85

Dimmable: NO

Width (mm): 30

Voltage In (Vac): 220~240

Frecuency (Hz): 50~60

Room Temperature (°C): -25~+50

Ingress Protection: IP20

Power factor: 0.95

### DOCUMENTS

[Data Sheet](#)

[Led Driver CC MP 80-500 SLIM multi-current up to 500mA 80W](#)

[CB](#)

[CCC \(China\)](#)

[CE](#)

[EAC \(RUSIA\)](#)

[Electromagnetic compatibility](#)

[ENEC \(Netherlands\)](#)

[Regulatory Compliance Mark for Australia](#)

[UKCA](#)