

**GTC80500 - 122214I**

**Led Driver CC MP 80-500 SLIM multi-current up to 500mA 80W**

March 09th, 2025, 16:59



## DESCRIPTION

Led Power supply Linear to incorporate with constant multi-current output selectable by DIP switch. High efficiency 93%. Output current from 350mA to 500mA. Protection against open circuit, short circuit, over load and over temperature. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI Code 122214I

## PRICE

Lot	P.V.P. excluding VAT
1	16,30€
5	14,82€
10	13,48€
72	12,48€

Continued on next page >>

GTC80500 - 122214I

**Led Driver CC MP 80-500 SLIM multi-current up to 500mA 80W**

## TECHNICAL SPECIFICATIONS

### SYMBOLS



### CERTIFICADOS

CB



EAC

(EMC)



UK  
CA

Weight: 140 Grams

### NOTES

ECO ERP Directives. DIP-SWITCH selectable output current from 350mA to 500mA

### OTHER FEATURES

Length (mm): 280

Width (mm): 30

High (mm): 21

Voltage In (Vac): 220~240

Intensidad Out (A): 0.35~0.5

Frecuency (Hz): 50~60

Power (W): 10~80

Room Temperature (°C): -25~+50

Critical Temperature (°C): 85

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.95

### DOCUMENTS

[Data Sheet](#)

[Led Driver CC MP 80-500 SLIM multi-current up to 500mA 80W](#)

[CB](#)

[CCC \(China\)](#)

[CE](#)

[EAC \(RUSIA\)](#)

[Electromagnetic compatibility](#)

[ENEC \(Netherlands\)](#)

[Regulatory Compliance Mark for Australia](#)

[UKCA](#)