

G503620

Led power CC Dimmable DALI SLD20-500IBD-UN hasta 500mA 20W

January 07th, 2025, 02:52



DESCRIPTION

Multi-current output selectable by DIP switch: 150mA 0.8-6W; 200mA 1-8W; 250mA 1.25-10W; 300mA 1.5-12W; 350mA 1.75-14W; 400mA 2-16W; 450mA 2-16W; 500mA 2.5-20. Output voltage range 5-40V. High efficiency. Quick connection terminals. Class I. Protection against open circuit, short circuit, overload and overtemperature. Automatic reset in case of failure. Very low ripple current throughout the regulation range. Warranty 5 years-0.84-0.95 power factor.

PRICE

	Lot	P.V.P. excluding VAT
	1	34,31€
	5	30,65€
	10	27,87€
	100	26,05€



Continued on next page >>

G503620

Led power CC Dimmable DALI SLD20-500IBD-UN hasta 500mA 20W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



Weight: 95 Grams

Packging: Box 1 Unit

NOTES

ECO Design ERP.To incorporate. Adjustable DALI or PUSH DIM. Output to constant current selectable from 150mA to 500mA per DIP switch.

OTHER FEATURES

Length (mm): 78,7

Width (mm): 41

High (mm): 22

Colour: White

Voltage In (Vac): 110~277

Voltage Out (Vdc): 27~40

Intensidad Out (A): 0.15~0.5

Frecuency (Hz): 50~60

Power (W): 4~20

Room Temperature (°C): -25~+50

Critical Temperature (°C): 90

Ingress Protection: IP20

Dimmable: DALI

Power factor: 0.84-0.95

DOCUMENTS

 [Data Sheet](#)

 [Led power CC Dimmable DALI SLD20-500IBD-UN hasta 500mA 20W](#)

 [C UR U.S. \(USA-Canada\)](#)

 [MEEI \(Hungary\)](#)

 [DALI2](#)