

G503620A

Led power CC Dimmable DALI SLD20-500ILD-UN hasta 500mA 20W

December 04th, 2024, 09:11



## DESCRIPTION

Multi-current output selectable by DIP2 switch: 150mA 0.8-6W; 200mA 1-8W; 250mA 1.25-10W; 300mA 1.5-12W; 350mA 1.75-14W; 400mA 2-16W; 450mA 2 -16W; 500mA 2.5-20. Output voltage range 5-40V. High efficiency. Quick connection terminals. Class II.<br>Protection against open circuit, short circuit, overload and overtemperature. Automatic reset in case of failure. Very low ripple current throughout the regulation range. Warranty 5 years-<br>0.84-0.95 power factor.

## PRICE

Lot	P.V.P. excluding VAT
1	37,23€
5	33,85€
10	30,77€
100	28,77€



Continued on next page >>

G503620A

Led power CC Dimmable DALI SLD20-500ILD-UN hasta 500mA 20W

## TECHNICAL SPECIFICATIONS

---

### SYMBOLS



**SELV**



Weight: 102 Grams

Packging: Box 1 Unit

### NOTES

---

ECO Design ERP Compliant. Independent use. Adjustable DALI2. Constant current output selectable from 150mA to 500mA by DIP switch.

### OTHER FEATURES

---

Length (mm): 103,1

Width (mm): 41

High (mm): 22

Colour: White

Voltage In (Vac): 110~277

Voltage Out (Vdc): 8~40

Intensidad Out (A): 0.15~0.5

Frecuency (Hz): 50~60

Power (W): 4~20

Room Temperature (°C): -20~+50

Critical Temperature (°C): 90

Ingress Protection: IP20

Dimmable: DALI

Power factor: 0.94-0.95

### DOCUMENTS

---

 [Data Sheet](#)

 [Led power CC Dimmable DALI SLD20-500ILD-UN hasta 500mA 20W](#)

 [C UR U.S. \(USA-Canada\)](#)

 [MEEI \(Hungary\)](#)

 [DALI2](#)