

G503620A

Led power CC Dimmable DALI SLD20-500ILD-UN hasta 500mA 20W

January 07th, 2025, 02:36



DESCRIPTION

Multi-current output selectable by DIP2 switch: 150mA 0.8-6W; 200mA 1-8W; 250mA 1.25-10W; 300mA 1.5-12W; 350mA 1.75-14W; 400mA 2-16W; 450mA 2 -16W; 500mA 2.5-20. Output voltage range 5-40V. High efficiency. Quick connection terminals. Class II.
Protection against open circuit, short circuit, overload and overtemperature. Automatic reset in case of failure. Very low ripple current throughout the regulation range. Warranty 5 years-
0.84-0.95 power factor.

PRICE

Lot	P.V.P. excluding VAT
1	37,23€
5	33,85€
10	30,77€
100	28,77€



Continued on next page >>

G503620A

Led power CC Dimmable DALI SLD20-500ILD-UN hasta 500mA 20W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



Weight: 102 Grams

Packging: Box 1 Unit

NOTES

ECO Design ERP Compliant. Independent use. Adjustable DALI2. Constant current output selectable from 150mA to 500mA by DIP switch.

OTHER FEATURES

Length (mm): 103,1

Width (mm): 41

High (mm): 22

Colour: White

Voltage In (Vac): 110~277

Voltage Out (Vdc): 8~40

Intensidad Out (A): 0.15~0.5

Frecuency (Hz): 50~60

Power (W): 4~20

Room Temperature (°C): -20~+50

Critical Temperature (°C): 90

Ingress Protection: IP20

Dimmable: DALI

Power factor: 0.94-0.95

DOCUMENTS

 [Data Sheet](#)

 [Led power CC Dimmable DALI SLD20-500ILD-UN hasta 500mA 20W](#)

 [C UR U.S. \(USA-Canada\)](#)

 [MEEI \(Hungary\)](#)

 [DALI2](#)