

**G503703D**

**Led Power Supply CC Mini-3.6-700 700mA 3.6W IP20**

December 03rd, 2024, 19:12



**DESCRIPTION**

Led power supply to incorporate with 700mA constant current output. Universal input voltage 100-240Vac. Output voltage from 2.5 to 5Vdc. Power range from 1.75 to 3.5W. Primary wiring with 18cm VDE 7726 0.5mm<sup>2</sup> cable and secondary wiring with 18cm UL1007 18AWG cable. Class II. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure.

**PRICE**

Lot	P.V.P. excluding VAT
1	6,10€
5	5,54€
10	5,03€
50	4,71€



Continued on next page >>

G503703D

Led Power Supply CC Mini-3.6-700 700mA 3.6W IP20

## TECHNICAL SPECIFICATIONS

---

### SYMBOLS



**SELV**



**RoHS**  
COMPLIANT

**CB**



Weight: 42 Grams

Packging: Box 1 Unit

### NOTES

---

ECO ERP Design. IP20. Constant current output 700mA.

### OTHER FEATURES

---

Length (mm): 53

Width (mm): 27

High (mm): 21

Colour: White

Voltage In (Vac): 100~240

Voltage Out (Vdc): 2.5~5

Intensidad Out (A): 0.7

Frecuency (Hz): 50~60

Power (W): 1.75~3.5

Room Temperature (°C): -20~+50

Critical Temperature (°C): 80

Life (Hours): 50000

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.50

### DOCUMENTS

---

 [Data Sheet](#)

 [Led Power Supply CC Mini-3.6-700 700mA 3.6W IP20](#)

 [CB](#)

 [Electromagnetic compatibility TÜV SÜD](#)

 [Safety TUV CERTIFIED](#)