

G503504A2

Led Power Supply CC Mini 350mA 4W

April 04th, 2025, 05:38



DESCRIPTION

IP20 Led power supply to incorporate with 350mA constant current output. Output voltage from 6 to 12Vdc. Power range from 2.1 to 4.2W. Wiring in primary and secondary with 18cm of UL1015 22AWG cable. Class II. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure.

PRICE

Lot	P.V.P. excluding VAT
1	6,37€
5	5,27€
10	4,78€
50	4,54€



Continued on next page >>

G503504A2

Led Power Supply CC Mini 350mA 4W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CB



UK
CA



Weight: 50 Grams

Packging: Box 1 Unit

NOTES

ECO Design ERP. IP20. 350mA constant current output

OTHER FEATURES

Length (mm): 53

High (mm): 21

Voltage In (Vac): 220~240

Intensidad In (A): 0.05

Frecuency (Hz): 50~60

Room Temperature (°C): -20~+60

Life (Hours): 50000

Dimmable: NO

Width (mm): 27

Colour: White

Voltage Out (Vdc): 6~12

Intensidad Out (A): 0.35

Power (W): 2.1~4.2

Critical Temperature (°C): 85

Ingress Protection: IP65

Power factor: 0.60

DOCUMENTS

[Data Sheet](#)

[Led Power Supply CC Mini 350mA 4W](#)

[ROHS](#)

[CB](#)

[CE](#)

[EMC TUV CERTIFIED](#)

[Safety TUV CERTIFIED](#)