

G503609

LED Power Supply CC SLT20-500IL-UN multi output current 150-500mA

March 09th, 2025, 17:09



DESCRIPTION

Led power supply for independent use with constant multi-current output selectable by DIP switch. Output voltage range 5-40V High efficiency 85%

PRICE

Lot	P.V.P. excluding VAT
1	19,25€
5	16,06€
10	14,60€
100	13,65€



Continued on next page >>

G503609

LED Power Supply CC SLT20-500IL-UN multi output current 150-500mA

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CB



Weight: 85 Grams

Packging: Box 1 Unit

NOTES

ECO Design ERP Compliant. Selectable constant output current from 150mA to 500mA by DIP switch. Class II

OTHER FEATURES

Length (mm): 85,3

Width (mm): 41

High (mm): 22

Colour: White

Voltage In (Vac): 110~277

Voltage Out (Vdc): 5~40

Intensidad Out (A): 0.15~0.5

Frecuency (Hz): 50~60

Power (W): 0.75~20

Room Temperature (°C): -25~+50

Critical Temperature (°C): 85

Life (Hours): 50000

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.70-0.90

DOCUMENTS

 [Data Sheet](#)

 [LED Power Supply CC SLT20-500IL-UN multi output current 150-500mA](#)

 [CCC \(China\)](#)

 [MEEI \(Hungary\)](#)

 [C UR U.S. \(USA-Canada\)](#)

 [Electromagnetic Compatibility TUV](#)