

LED TECHNOLOGY > Electronic Led Power Supplies > LED Power Supplies Constant Current  
Led Power Supplies Dip-Switch multicurrent

G503611B

LED Power Supply CC SLT25-600IB-E multi output current 250-600mA

December 04th, 2024, 08:45



## DESCRIPTION

Led power supply to incorporate with multi-current output selectable by DIP switch. Output voltage range 27-42V High efficiency 87%<br>. Class II.<br>250mA 6.7-10.5W; 300mA 8.1-12.3W; 350mA 9.4-14.7W; 400mA 10.8-16.8W; 450 mA 12.2-18.9W; 500mA 13.5-21W; 550mA 14.8-23.1W; 600mA 16.2-25.2W. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure. Warranty 5 years.<br>

## PRICE

	Lot	P.V.P. excluding VAT
	1	14,39€
	5	11,99€
	10	10,91€
	100	10,19€



Continued on next page >>

G503611B

**LED Power Supply CC SLT25-600IB-E multi output current 250-600mA**

## TECHNICAL SPECIFICATIONS

---

### SYMBOLS



**SELV**



### CERTIFICADOS



Weight: 88 Grams

Packging: Box 1 Unit

## NOTES

---

Selectable constant output current from 250mA to 600mA per DIP switch. Model without blue caps. To incorporate

## OTHER FEATURES

---

Length (mm): 66,7

Width (mm): 41

High (mm): 22

Colour: White

Voltage In (Vac): 220~240

Voltage Out (Vdc): 27~42

Intensidad Out (A): 0.25~0.6

Frecuency (Hz): 50~60

Power (W): 6.7~25.2

Room Temperature (°C): -20~+50

Critical Temperature (°C): 90

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.8-0.9

## DOCUMENTS

---

 [Data Sheet](#)