

G503611

**LED Power Supply CC SLT25-600IL-E multi output current 250-600mA**

December 04th, 2024, 09:14



**DESCRIPTION**

Led power supply for independent use with constant multi-current output selectable by DIP switch. Output voltage range 27-42V High efficiency 87%. Class II. <br>250mA 6.7-10.5W; 300mA 8.1-12.3W; 350mA 9.4-14.7W; 400mA 10.8-16.8W; 450 mA 12.2-18.9W; 500mA 13.5-21W; 550mA 14.8-23.1W; 600mA 16.2-25.2W. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure. Warranty 5 years.

**PRICE**

Lot	P.V.P. excluding VAT
1	15,83€
5	13,20€
10	11,99€
100	11,21€



Continued on next page >>

G503611

**LED Power Supply CC SLT25-600IL-E multi output current 250-600mA**

## TECHNICAL SPECIFICATIONS

---

### SYMBOLS



**SELV**



### CERTIFICADOS



Weight: 80 Grams

Packging: Box 1 Unit

### NOTES

---

ECO Design ERP Compliant. Selectable constant output current from 250mA to 600mA by DIP switch.

### OTHER FEATURES

---

Length (mm): 85,3

Width (mm): 41

High (mm): 22

Colour: White

Voltage In (Vac): 220~240

Voltage Out (Vdc): 27~42

Intensidad Out (A): 0.25~0.6

Frecuency (Hz): 50~60

Power (W): 6.7~25.2

Room Temperature (°C): -20~+50

Critical Temperature (°C): 90

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.8-0.9

### DOCUMENTS

---

 [Data Sheet](#)

 [LED Power Supply CC SLT25-600IL-E multi output current 250-600mA](#)

 [MEEI \(Hungary\)](#)