

G503635A

LED Power Supply CC SLT351000ILD-UN DC power supply up to 1000mA

January 08th, 2025, 07:37



DESCRIPTION

Multi-current output selectable by DIP switch: 250mA 0.75-8.75 W; 300mA 0.9-10.5W; 350mA 1.05-12.5W; 400mA 1.2-14W; 450mA 1.35- 15.75W; 500mA 1.7-17.5W; 550mA 1.65-19.25W; 600mA 1.8-21W; 650mA 1.95-22.75W; 700mA 2.1-24.5W; 750mA 2, 25-26.25W; 800mA 2.4-28W; 850mA 2.55-29.75W; 900mA 2.7-31.5W; 950mA 2.85-33.25W 1000mA 3-35W Output voltage range 5- 40V. High efficiency. Quick connection terminals. Class I.
Protection against open circuit, short circuit, overload and overtemperature. Automatic reset in case of failure. Very low ripple current throughout the regulation range. Warranty 5 years-
0.84-0.95 power factor.

PRICE

Lot	P.V.P. excluding VAT
1	41,15€
5	37,40€
10	34,01€
100	31,79€



G503635A

LED Power Supply CC SLT351000ILD-UN DC power supply up to 1000mA

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



Weight: 183 Grams

Packging: Box 1 Unit

NOTES

ECO Design ERP Compliant. Independent use. Adjustable DALI or PUSH DIM. Output to constant current selectable from 250mA to 1000mA by DIP switch.

OTHER FEATURES

Length (mm): 139

Width (mm): 42

High (mm): 29,8

Colour: White

Voltage In (Vac): 110~277

Voltage Out (Vdc): 8~42

Intensidad Out (A): 0.25~1

Frecuency (Hz): 50~60

Power (W): 5.2~35

Room Temperature (°C): -20~+50

Critical Temperature (°C): 90

Ingress Protection: IP20

Dimmable: DALI

Power factor: 0.95

DOCUMENTS

 [Data Sheet](#)

 [LED Power Supply CC SLT351000ILD-UN DC power supply up to 1000mA](#)

 [C UR U.S. \(USA-Canada\)](#)

 [MEEI \(Hungary\)](#)

 [DALI2](#)