

G503635A

**LED Power Supply CC SLT351000ILD-UN DC power supply up to 1000mA**

December 04th, 2024, 19:55



**DESCRIPTION**

Multi-current output selectable by DIP switch: 250mA 0.75-8.75 W; 300mA 0.9-10.5W; 350mA 1.05-12.5W; 400mA 1.2-14W; 450mA 1.35- 15.75W; 500mA 1.7-17.5W; 550mA 1.65-19.25W; 600mA 1.8-21W; 650mA 1.95-22.75W; 700mA 2.1-24.5W; 750mA 2, 25-26.25W; 800mA 2.4-28W; 850mA 2.55-29.75W; 900mA 2.7-31.5W; 950mA 2.85-33.25W 1000mA 3-35W Output voltage range 5- 40V. High efficiency. Quick connection terminals. Class I.<br>Protection against open circuit, short circuit, overload and overtemperature. Automatic reset in case of failure. Very low ripple current throughout the regulation range. Warranty 5 years-<br>0.84-0.95 power factor.

**PRICE**

Lot	P.V.P. excluding VAT
1	41,15€
5	37,40€
10	34,01€
100	31,79€



G503635A

**LED Power Supply CC SLT351000ILD-UN DC power supply up to 1000mA**

## TECHNICAL SPECIFICATIONS

---

### SYMBOLS



**SELV**



Weight: 183 Grams

Packging: Box 1 Unit

### NOTES

---

ECO Design ERP Compliant. Independent use. Adjustable DALI or PUSH DIM. Output to constant current selectable from 250mA to 1000mA by DIP switch.

### OTHER FEATURES

---

Length (mm): 139

Width (mm): 42

High (mm): 29,8

Colour: White

Voltage In (Vac): 110~277

Voltage Out (Vdc): 8~42

Intensidad Out (A): 0.25~1

Frecuency (Hz): 50~60

Power (W): 5.2~35

Room Temperature (°C): -20~+50

Critical Temperature (°C): 90

Ingress Protection: IP20

Dimmable: DALI

Power factor: 0.95

### DOCUMENTS

---

 [Data Sheet](#)

 [LED Power Supply CC SLT351000ILD-UN DC power supply up to 1000mA](#)

 [C UR U.S. \(USA-Canada\)](#)

 [MEEI \(Hungary\)](#)

 [DALI2](#)