

G503805

LED Power Supply CC SLT45-1050IL-E multi output current 700-1050mA

December 04th, 2024, 09:09



DESCRIPTION

Led power supply for independent use with constant multi-current output selectable by DIP switch. Output voltage range 27-42V High efficiency. Class II. Quick connection terminals. Selectable outputs: 700mA 18.9-29.4W; 750mA 20.3-31.5W; 800mA 21.6-33.6W; 850mA 22.9-35.7W; 900mA 24.3-37.8W; 950mA 25.6-39.9W; 1000mA 27-42W; 1050mA 28.3-42W. Protection against open circuit, short circuit, overload and overtemperature. Automatic reset. 5 year warranty

PRICE

Lot	P.V.P. excluding VAT
1	17,46€
5	15,87€
10	14,44€
50	13,49€



G503805

LED Power Supply CC SLT45-1050IL-E multi output current 700-1050mA

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



RoHS
COMPLIANT



Weight: 148 Grams

Packging: Box 1 Unit

NOTES

ECO Design ERP Compliant. Selectable constant output current from 700mA to 1050mA by DIP switch.

OTHER FEATURES

Length (mm): 139

High (mm): 29,8

Voltage In (Vac): 220~240

Intensidad Out (A): 0.7~1.05

Power (W): 18.9~42

Critical Temperature (°C): 85

Dimmable: NO

Width (mm): 42

Colour: White

Voltage Out (Vdc): 27~42

Frecuency (Hz): 50~60

Room Temperature (°C): -25~+50

Ingress Protection: IP20

Power factor: 0.95

DOCUMENTS

 [Data Sheet](#)

 [LED Power Supply CC SLT45-1050IL-E multi output current 700-1050mA](#)

 [CCC \(China\)](#)

 [MEEI \(Hungary\)](#)

 [Regulatory Compliance Mark for Australia](#)