

G5037080

LED Power Supply CC SLT80-700IL-EU multi-current up to 700mA 80W

January 07th, 2025, 02:02



DESCRIPTION

Led Power to incorporate with constant current multi-current output by DIP switch Class I. Quick connection terminals. 325mA 39-80W; 350mA 42-80W; 375mA 45-80W; 400mA 48-80W; 425mA 34-80W; 450mA 36-80W; 500mA 40-80W; 525mA 36.8-80W; 550mA 38.5-80W; 575mA 40.3-80W; 600mA 72-80W; 625mA 37.5-80W; 650mA 39--80W; 675mA 40.5 -80W; 700mA 42-80W.

Protection against open circuit, short circuit, over load and over temperature. Rearmament.

PRICE

Lot	P.V.P. excluding VAT
1	20,18€
5	18,34€
10	16,67€
50	15,60€



G5037080

LED Power Supply CC SLT80-700IL-EU multi-current up to 700mA 80W

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS

Weight: 230 Grams

Packging: Box 1 Unit

NOTES

ECO Design ERP Compliant. Selectable constant output current from 325mA to 700mA by DIP switch.

OTHER FEATURES

Length (mm): 280

Width (mm): 30

High (mm): 22

Colour: White

Voltage In (Vac): 220~240

Voltage Out (Vdc): 40~246

Intensidad Out (A): 0.32~0.7

Frecuency (Hz): 50~60

Power (W): 34~80

Room Temperature (°C): -25~+50

Critical Temperature (°C): 90

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.9

DOCUMENTS

 [Data Sheet](#)

 [LED Power Supply CC SLT80-700IL-EU multi-current up to 700mA 80W](#)

 [MEEI \(Hungary\)](#)