

G503525B

Led Power Supply CC V8 700mA 25W

August 24th, 2024, 14:09



DESCRIPTION

Led power supply for independent use at constant current 700mA. The output voltage goes from 18 to 36Vdc and the power range is from 12.6 to 25W. Class II. Screw terminals for cables from 0.75 to 2.5mm² section. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure.

PRICE

	Lot	P.V.P. excluding VAT
	1	8,06€
	5	6,71€
	10	6,10€
	50	5,69€

Continued on next page >>

G503525B

Led Power Supply CC V8 700mA 25W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CB



**UK
CA**



Weight: 85 Grams

NOTES

ECO Design ERP Compliant. 700mA constant current output

OTHER FEATURES

Length (mm): 127

High (mm): 28

Voltage In (Vac): 220~240

Intensidad In (A): 0.15

Frecuency (Hz): 50~60

Room Temperature (°C): -20~+50

Life (Hours): 30000

Dimmable: NO

Width (mm): 43

Colour: White

Voltage Out (Vdc): 18~36

Intensidad Out (A): 0.7

Power (W): 12.6~25

Critical Temperature (°C): 80

Ingress Protection: IP20

Power factor: 0.95

DOCUMENTS

 [Data Sheet](#)

 [Led Power Supply CC V8 700mA 25W](#)

 [ROHS](#)

 [CB](#)

 [CE](#)

 [EMC TUV CERTIFIED](#)

 [Safety TUV CERTIFIED](#)